

SMARTCUT FC3550

FLATBED CUTTER



Specifications

Model	FC3550 Flatbed Cutter
Cutting Area	350x500mm
Max. Cutting Speed	1000 mm/s
Max. Cutting Force	1000 g
Max. Cutting Thickness	1.2 mm
Stand	NO
Type of cutting head	Double (Standard)
Adsorption system	Built-inside Vacuum
Interface	USB/Flash Drive/WiFi/LAN
ARMS System	CCD Camera
Drive System	Servo System
Resolution	0.0125 mm
Working Atmosphere	Temperature: 0 to 35°C, Relative Humidity: 35% to 95% (non-condensing)
Power Supply	AC100~240V/50~60Hz/10A
Machine Size	670x970x300mm
Unit Dimensions	770x1070x480mm
Unit G.W	70kg
Dimensions and G.W for Vacuum	NO



SMART TOUCH SCREEN

Simple operation, smooth performance.



HIGH-DEFINITION CAMERA

Material-agnostic, precise positioning.



SERVO SYSTEM + DUAL LINEAR GUIDE RAIL STRUCTURE

High speed, low noise, high-efficiency and more stable cutting performance.



Utilizes a honeycomb-structured platform, sturdy and durable.



VACUUM ADSORPTION

Low noise, strong suction force, ensures material flatness, and smooth cutting.



MULTI-PORT OUTPUT

Supports multiple connection ports including USB, Flash Drive, LAN, WiFi.

+91 98336 63100 | +91 93243 76523

sales@ashwinenterprises.org | www.ashwinenterprises.org

Unit no.: 35/G, Apollo Industrial Estate, Behind Holy Family School,
Off. Mahakali Caves Road, Andheri East, Mumbai-400093.

Regional Office : New Delhi | Ahmedabad | Bengaluru | Kerala | Chennai
Madurai | Coimbatore | Hyderabad | Andhra Pradesh | Nagpur | Surat